

● TYPE 2

Type 2 charging, up to 22 kW.

A wall-mounted Type 2 smart charger from 3.3 kW to 22 kW with a 5 m cable, RFID or app authentication, built-in Class 1 metering and OCPP 1.6J.

3.3 to 22 kW

Single or three phase, 3.3/7.4 kW or 11/22 kW output

RFID or app

Authenticate with a card or from the phone, OCPP 1.6J throughout

Protection built in

Ground fault detection, surge protection and emergency stop



01

Specifications

TYPE 2 · WALL MOUNTED

One unit, four ratings

3.3 or 7.4 kW single phase, 11 or 22 kW three phase — the same wall-mounted enclosure and the same back office.

Metering inside

A Class 1 energy meter is built into the charger for accurate session billing and site load management.

Connect any way

4G, WiFi and Ethernet on board with OCPP 1.6J, so the charger reaches any CPO platform.

Two ways in

RFID card or mobile app authentication, with an RGB LED showing charge state at a glance.

CHARGING

Power rating	3.3 / 7.4 kW or 11 / 22 kW
Connector	Type 2, 5 m cable
Mounting	Wall mounted
Design rating	IP 55

LOAD MANAGEMENT

Energy meter	Built in, Class 1
Indication	RGB LED

BUILT-IN SAFETY

Over current	Yes
Over / under voltage	Yes
Ground fault detection	Yes
Surge protection	Yes
Emergency stop	Button on unit

CONNECTIVITY

Links	4G, WiFi, Ethernet
Protocol	OCPP 1.6J
Authentication	Mobile app or RFID

COMPLIANCE

OCPP 1.6 compliant · Class 1 metering · IP 55

contact@techovn.com

+91 98919 21532